

XeLAN

XeLAN CAT6A UFTP 4 Pair Cable Dca -
Box of 305m, Violet

Part Number: 5000-0001



Features:

Fast feed box

Sequential metre markings

Euroclass Dca-s1a-d2-a1

Specification:

Category:	6A (IEC)
Overall screening:	None
Conductor screening:	Foil
Outer sheath colour:	Violet
Reaction-to-fire class according to EN 13501-6:	Dca
Smoke development class according to EN 13501-6:	s1a
Euro class flaming droplets/particles according to EN 13501-6:	d2
Euro class acidity according to EN 13501-6:	a1
AWG-size:	23
Specification core insulation:	PE
Core identification:	Colour
Outer sheath material:	Copolymer, thermoplastic (LS0H)
Diameter of conductor:	0.56 mm
Halogen free (acc. EN 60754-1/2):	Yes
Flame retardant:	In accordance with EN 60332-1-2 and EN 50399
Low smoke (acc. BS EN 61034-2):	Yes
Outer diameter approx.:	7.5 mm
Installation Temperature Range:	0 ... 60 °C
Operating Temperature Range:	-20 ... 60 °C
Conductor category:	Class 1 = solid
Total number of cores:	8
Core insulation:	PE(Skin-Foam-Skin)
Conductor surface:	Bare